

## Instructions for installing BreezeGuard™ Screens

To install a BreezeGuard™ screen:

- Open the vehicle door.
- Roll the window most of the way down. Leave about 2" of glass up.
- Position yourself on the inside of the door.
- Insert the anchor attached to the bottom of the screen (the things with black tape) between the glass and the frame of the vehicle door. You may have to pull the rubber window gasket away a little bit to do this. I have found using a business card, gift card or library card might make this task easier.
- The metal BreezeGuard label faces to the outside of the vehicle away from the dog.
- Take each of the Velcro straps (which are laced through one of the slots in the screen) and wrap it around the door frame as tight as you can. With practice, you will quickly find the right fit for your vehicle.
- Try to line up both parts of the strap directly on top of each other. (Precision is not essential but it looks nicer.)
- Readjust all straps until the screen is securely fastened and all straps are tight.

Note: the soft side of the strap goes against the paint of the vehicle.

The windows should move up and down freely. Some car models have tighter window gaskets with less tolerance. If the window drags and you cannot adjust the BreezeGuard® Screens to allow free window movement, DO NOT FORCE the window motor beyond its capacity. You may still use the BreezeGuards with the windows rolled down.

**"Do not leave pet unattended in vehicle"**

If you have any difficulties, give me a ring at 253.222.5214 and I will talk you through the installation process.

Thank you again for your purchase.

Sue Stipanovich  
MuttManagers, LLC